

## PLUG CAT.5E



<b>Product Type</b>	PLUG RJ-45
---------------------	------------

<b>Product Family</b>	MultiLan
-----------------------	----------

<b>Standard</b>	RoHS Compliant
-----------------	----------------

### Applications

<b>Installation Environment</b>	Indoor
---------------------------------	--------

<b>Operation Environment</b>	Non Aggressive
------------------------------	----------------

### Compatibility

<b>Warranty</b>	12 months
-----------------	-----------

<b>Identification</b>	Manufacturer logotype in the product
-----------------------	--------------------------------------

<b>Trace</b>	Packing with code of the product, date of fabrication and contact of manufacturer
--------------	---

### Constructive characteristic

<b>High</b>	8,0mm
-------------	-------

<b>Width</b>	11,7mm
--------------	--------

<b>Depth</b>	21,5mm internal 22,5mm external
--------------	------------------------------------

<b>Weight</b>	0,002kg
---------------	---------

<b>Color</b>	Transparent
--------------	-------------

<b>Connector Type</b>	RJ-45
-----------------------	-------

<b>Cable type</b>	U/UTP
-------------------	-------

<b>Conductor diameter</b>	26 up to 22 AWG
---------------------------	-----------------

<b>Material of electrical contact</b>	8-way phosphor bronze with 100µin (2,54 µm) of nikel and 50µin (1,27 µm) of gold
---------------------------------------	--

<b>Material of Product body</b>	Transparent thermoplastic material UL 94V-0
---------------------------------	---

<b>Installation Temperature</b>	20°C
---------------------------------	------

<b>StorageTemperature</b>	-40 C up to +70 C
---------------------------	-------------------

**Operation Temperature** -10°C to +60°C

---

**Package**

---

**Package Type** Transparent plastic bag (500 pieces).

---

**Minimum order quantity** 01 package

---

**Associated Solutions** Residential cabling

---

**Standards and Certifications**

---

**Standard** EIA/TIA 568 C.2 and Addendums

ISO/IEC 11801

NBR 14565

FCC 68.5

---

**Certification** UL E173971

ISO9001/ISO14001 416253

---