



Category 6 Modular Plug



Specification :

Application : Meets or exceeds TIA/EIA-568B.2-1 and TIA/EIA 568-C Category 6 and ISO/IEC 11801: 2002 Class E, specifications
 Housing Material : Polycarbonate, UL 94V-2 NO Poison.
 Structure : 2 layer with pre-insert bar.
 Material Contact : Phosphor Bronze with over 50 micro-inches gold plating over nickel plate
 Wire : both solid and stranded size 22-26 AWG

PART NO.	DESCRIPTION
C67001	CAT6 RJ45 Modular Plug unshield, 8 pin, 2 layer w/Pre-Insert Bar
C67002	CAT6 RJ45 Modular Plug shield, 8 pin, 2 layer w/Pre-Insert Bar

Category 6A Modular Plug



SPECIFICATION MECHANICAL :

- Housing Material: Polycarbonate, UL 94V-2 NO Poison.
- Material Contact: 6U" Below Brass. 15U" Above Phosphor Bronze.
- Contact area Plated gold 50u", the other area plated gold over FU"
- Contact area plated Nickel over 60u", the other area plated Nickel over 30u"
- Housing Color: Transparence.
- Operation Temperature: -40 C° to 80 C°

PART NO.	DESCRIPTION
BC-C6A01	CAT6A RJ45 Modular Plug unshield, 3 piece, 8P8C-F,2 Layer
BC-C6A02	CAT6A RJ45 Modular Plug Shield,3 piece, 8P8C-F,2 Layer