



CATALOG

GUIDE

MODULE OF FIBER OPTIC

- 155Mbps and 1.25G SFP Module
- 10G SFP+ and 10G XFP Module
- 40G QSFP Module
- 10G SFP+ DAC Passive and Active Cable
- 10G SFP+ AOC and 40G QSFP AOC Cable
- 40G-10G AOC and DAC Cable

1.25G SFP Module Fiber Optic

PRODUCT FEATURES

- Up to 1.25Gb/s data links
- FP laser transmitter and PIN photo-detector
- Singlemode and Multimode Fiber
- Hot-pluggable SFP footprint
- Duplex LC/UPC type pluggable optical interface
- Low power dissipation
- Metal enclosure, for lower EMI
- RoHS compliant and lead-free
- Single + 3.3V power supply
- Compliant with SFF-8472

Certificate with ISO9001, UL, FCC, CE, RoHs, CB, FDA

COMPATIBLE WITH BRAND AS BELOW.

CISCO, BELLCOMMS, 3COM, ALLIED, TELESYN, LINK, ZYXEL

Picture	Part No. / Descriptions	Best Seller
	BC-GLC-T 1000Base-T SFP compatible with Cisco	
	CTM-LC0500-MM SFP 1.25G 850nm, Multimode LC,SX transceiver 550 Meters CISCO compatible	
	CTM-LC02KM-MM SFP 1.25G 1310nm, Multimode LC, SX transceiver 2Km CISCO compatible	
	CTS-LC0010-SM SFP 1.25G, 1310nm, Singlemode LC, LX/LHtransceiver 10Km CISCO compatible	
	CTS-LC0020-SM SFP 1.25G, 1310nm, Singlemode LC, LX/LHtransceiver 20Km CISCO compatible	
	BC-GLC-LHX-SMCTS-LC0040-SM SFP 1.25G 1310nm, Singlemode LC, LX/LHtransceiver 40Km, CISCO compatible	
	CTS-LC0080-SM SFP 1.25G 1550nm, Singlemode LC, LX/LHtransceiver 80Km, CISCO compatible	
	CTS-LC00120-SM SFP 1.25G 1550nm, Singlemode LC, LX/LHtransceiver 120Km, CISCO compatible	

COMPATIBLE WITH BRAND AS BELOW.

HP with part number refer only.

Picture	Part No. / Descriptions	Best Seller
	CTM-LCHP50-MMSFP 1.25G, Mini GBIC 850nm Multimode 1000-Base -SX/550m, compatible HP ProCurve (J4858C)	
	CTS-LCHP10-SM SFP 1.25G, Mini GBIC 1310nm Singlemode 1000-Base-LX/10Km, compatible HP ProCurve (J4859C)	
	BCHP-8512-02D-H3 HP X120 1G SFP LC SX Transceiver (JD118B), 850nm, 550m, with DDM, Compatible HP	
	BCHP-1312-10D-H3 HP X120 1G SFP LC LX Transceiver (JD119B), 1310nm, 10km, with DDM, Compatible HP	

COMPATIBLE WITH BRAND AS BELOW.

CISCO, BELLCOMMS, 3COM, ALLIED, TELESYN, LINK, ZYXEL

Picture	Part No. / Descriptions	Best Seller
	BC-BL3512-10 SFP 1.25G, WDM, Tx 1310/ Rx1550nm, SM, SingleFiber, 10Km, CISCO compatible	
	BC-BL5312-10 SFP 1.25G, WDM, Tx 1550/ Rx1310nm, SM, SingleFiber, 10Km, CISCO compatible	
	BC-BL3512-20 SFP 1.25G, WDM, Tx 1310/ Rx1550nm, SM, SingleFiber, 20Km, CISCO compatible	
	BC-BL5312-20 SFP 1.25G, WDM, Tx 1550/ Rx1310nm, SM, SingleFiber, 20Km, CISCO compatible	
	BC-BL3512-40 SFP 1.25G, WDM, Tx 1310/ Rx1550nm, SM, SingleFiber, 40Km, CISCO compatible	
	BC-BL5312-40 SFP 1.25G, WDM, Tx 1550/ Rx1310nm, SM, SingleFiber, 40Km, CISCO compatible	
	BC-BL3512-80 SFP 1.25G, WDM, Tx 1310/ Rx1550nm, SM, SingleFiber, 80Km, CISCO compatible	
	BC-BL5312-80 SFP 1.25G, WDM, Tx 1550/ Rx1310nm, SM, SingleFiber, 80Km, CISCO compatible	

155 Mbps SFP Module Fiber Optic

PRODUCT FEATURES

- Up to 155Mb/s data links
- FP laser transmitter and PIN photo-detector
- Up to 2km and 10Km on 9/125µm SMF
- Hot-pluggable SFP footprint
- Duplex LC/UPC type pluggable optical interface
- Low power dissipation
- Metal enclosure, for lower EMI
- RoHS compliant and lead-free
- Support Digital Diagnostic Monitoring interface
- Single +3.3V power supply
- Compliant with SFF-8472

COMPATIBLE WITH BRAND AS BELOW.

CISCO, BELLCOMMS, 3COM, ALLIED, TELESYN, LINK, ZYXEL

Picture	Part No. / Descriptions	Best Seller
	SFP-100FX02-MM SFP 155Mb/s 100Base-FX Multimode 1310 nm 2Km.compatible with Cisco	
	SFP-100FX10-SM SFP 155MB/s 100Base-LX Singlemode 1310 nm 10Km. compatible with Cisco	

10G SFP+ Module Fiber Optic

PRODUCT FEATURES

- Duplex LC Connector
- Support hot-pluggable
- Metal with lower EMI
- Excellent ESD protection
- RoHS Compliant and lead-Free
- Compliant with IEEE802.3ae
- Compliant with SFP+ MSA:SFF-8431 Rev4.1
- Digital diagnostic compatible with SFF-8472 Rev11.0
- Single 3.3V power supply and low power dissipation <1.5W

Certificate with ISO9001, UL, FCC, CE, RoHS, CB, FDA

Picture	Part No. / Descriptions	Best Seller
	SFP-10G-30 SFP+ LC, 10G Multimode 850nm, 300meters COMPATIBLE : Cisco, HP, Alcatel-lucent, Extreme, Huawei, ZTE, Juniper, Brocade, D-LINK, H3C, Netgear, MikroTik, Arista.	
	SFP-10G-10 SFP+ LC, 10G SingleMode 1310nm, 10Km COMPATIBLE : Cisco, HP, Ciena, Alcatel-lucent, Extreme, Huawei, ZTE, Juniper, Brocade, D-LINK, H3C, Netgear, MikroTik, 3com, Intel.	
	SFP-10G-40 SFP+ LC, 10G SingleMode 1550nm, 40Km COMPATIBLE : Cisco, Ciena, Alcatel-lucent, Huawei, ZTE, Juniper, H3C,D-LINK.	
	SFP-10G-80 SFP+ LC, 10G SingleMode 1550nm, 80Km COMPATIBLE : Cisco, Ciena, Alcatel-lucent, Huawei, ZTE, Juniper, H3C,D-LINK.	

COMPATIBLE WITH BRAND AS BELOW.
HP with part number refer only

Picture	Part No. / Descriptions	Best Seller
	BCHP-8596-02D-H3 HP X130 10G SFP+ LC SR Transceiver (JD092B), 850nm, 300m, Compatible HP	
	BCHP-1396-10D-H3 HP X130 10G SFP+ LC LR Transceiver (JD094B),1310nm, 10km, Compatible HP	

10G XFP Module Fiber Optic

PRODUCT FEATURES

- Duplex LC Connector
- Support hot-pluggable
- Metal with lower EMI
- Excellent ESD protection
- XFP MSA compliant
- RoHS compliant and Lead-Free
- Compatible with IEEE 802.3ae
- ITU-T G.959, G.691 compliant GR-253-CORE compliant

Certificate with ISO9001, UL, FCC, CE, RoHS, CB, FDA

COMPATIBLE WITH BRAND AS BELOW.
Cisco, Alcatel-lucent, Juniper, Huawei, Extreme

Picture	Part No. / Descriptions	Best Seller
	BC-8596-02D XFP LC, 10G Multimode 850nm, 300meters	
	BC-1396-10D XFP LC, 10G SingleMode 1310nm, 10Km	
	BC-1596-40D XFP LC, 10G SingleMode 1550nm, 40Km	
	BC-1596-80D XFP LC, 10G SingleMode 1550nm, 80Km	

COMPATIBLE WITH BRAND AS BELOW.
HP with part number refer only

Picture	Part No. / Descriptions	Best Seller
	BCHP-8596-02D HP X130 10G XFP LC SR Transceiver (JD117B), 850nm, 300m, Compatible HP	
	BCHP-1396-10D HP X135 10G XFP LC ER Transceiver (JD108B), 1310nm, 10km, Compatible HP	

40 Gb/s QSFP+ PSM4 Module Optical Transceiver

PRODUCT FEATURES

- 4 independent full-duplex channels Up to 10.3125Gbps data rate per channel
- MTP/MPO optical connector
- QSFP MSA compliant
- Digital diagnostic capabilities
- Links up to 2 km using single mode fiber
- Single +3.3V power supply
- Operating case temperature: 0~70C
- RoHS-6 compliant
- XLPI Electrical Interface Compliant with IEEE 802.3ba-2010
- Compliant with QSFP+ MSA: SFF-8436
- Support optical interoperability with IEEE 802.3ae 10GBASE-LR modules

APPLICATIONS

- 40G Ethernet
- Infiniband 4X SDR DDR QDR
- 40G Telecom connections

REGULATORY COMPLIANCE

- ESD to the Electrical PINs: compatible with MIL-STD-883E Method 3015.7
- Immunity compatible with IEC 61000-4-3
- EMI compatible with FCC Part 15 Class B EN55022 Class B (CISPR 22B) VCCI Class B
- Laser Eye Safety compatible with FDA 21CFR 1040.10 and 1040.11 EN60950, EN (IEC) 60825-1,2
- RoHS compliant with 2002/95/EC 4.1&4.2 2005/747/EC

Certificate with ISO9001, UL, FCC, CE, RoHs, CB, FDA

Picture	Part No. / Descriptions	Best Seller
	BC-APQPSR4CM01A 40 Gb/s QSFP+ MPO Optical Transceiver 850nm, 100 Metes	Order 1 week
	BC-APQPLR4CM20 40 Gb/s QSFP+ MPO Optical Transceiver 1310nm, 2Km	Order 1 week

** Other length with depend on customer requested.

40 Gb/s QSFP+ PSM4 Module Optical Transceiver

PRODUCT FEATURES

- 4 independent full-duplex channels Up to 10.3125Gbps data rate per channel
- MTP/MPO optical connector
- QSFP MSA compliant
- Digital diagnostic capabilities
- Links up to 10 km using single mode fiber
- Single +3.3V power supply
- Operating case temperature: 0~70C
- RoHS-6 compliant
- XLPI Electrical Interface Compliant with IEEE 802.3ba-2010
- Compliant with QSFP+ MSA: SFF-8436
- Support optical interoperability with IEEE 802.3ae 10GBASE-LR modules

APPLICATIONS

- 40G Ethernet
- Infiniband 4X SDR DDR QDR
- 40G Telecom connections

REGULATORY COMPLIANCE

- ESD to the Electrical PINs: compatible with MIL-STD-883E Method 3015.7
- Immunity compatible with IEC 61000-4-3
- EMI compatible with FCC Part 15 Class B EN55022 Class B (CISPR 22B) VCCI Class B
- Laser Eye Safety compatible with FDA 21CFR 1040.10 and 1040.11 EN60950, EN (IEC) 60825-1,2
- RoHS compliant with 2002/95/EC 4.1&4.2 2005/747/EC

Certificate with ISO9001, UL, FCC, CE, RoHs, CB, FDA

Picture	Part No. / Descriptions	Best Seller
	BC-APQPLR4CM1A 40Gb/s QSFP+ MPO Optical Transceiver 1310nm, 10Km	Order 1 week

** Other length with depend on customer requested.

40 Gb/s QSFP+ LR4 Module Optical Transceiver

PRODUCT FEATURES

- 4 CWDM lanes MUX/DEMUX design
- 4 independent full-duplex channels Up to 11.3Gbps data rate per wavelength
- 4 CWDM channels are 1271, 1291, 1311 and 1331 nm
- Single +3.3V power supply
- QSFP+ MSA compliant
- Up to 10km transmission
- Operating case temperature: 0~70C
- RoHS compliant
- Compliant with IEEE802.3ba
- Compliant with QSFP+ MSA: SFF-8436

APPLICATIONS

- 40G Ethernet
- Infiniband 4X SDR DDR QDR
- 40G Telecom connections

REGULATORY COMPLIANCE

- ESD to the Electrical PINs: compatible with MIL-STD-883E Method 3015.7
- ESD to the LC Receptacle: compatible with IEC 61000-4-2 GR-1089-CORE
- Immunity compatible with IEC 61000-4-3
- EMI compatible with FCC Part 15 Class B EN55022 Class B (CISPR 22B) VCCI Class B
- Laser Eye Safety compatible with FDA 21CFR 1040.10 and 1040.11 EN60950, EN (IEC) 60825-1,2
- RoHS compliant with 2002/95/EC 4.1&4.2 2005/747/EC

Certificate with ISO9001, UL, FCC, CE, RoHs, CB, FDA

Picture	Part No. / Descriptions	Best Seller
	BC-APQPLR4CL1AA 40 Gb/s QSFP+ LC Optical Transceiver 1310nm, 10Km	Order 1 week

** Other length with depend on customer requested.

10G SFP+ DAC Active Copper Cable

PRODUCT FEATURES

- Truly broadband - operates from 1 to 10.5 Gb/s
- Support hot-pluggable
- Available in lengths from 1m to 15m
- 360 degree cable braid crimp and enhanced EMI skirt
- Excellent ESD protection
- Single 3.3V power supply
- RoHS Compliant and Lead-Free
- Compliant with SFF-8472 Rev 11.1
- Compliant with SFP+ MSA: SFF-8431 Rev4.1
- Wire/Cable Type Twinax

APPLICATIONS

- 1/10GbE
- 1/2/4/8x FC
- Infiniband 1X SDR DDR QDR
- Proprietary Interconnects

REGULATORY COMPLIANCE

- ESD to the Electrical PINs: compatible with MIL-STD-883E Method 3015.7
- Immunity compatible with IEC 61000-4-3
- EMI compatible with FCC Part 15 Class B EN55022 Class B
- RoHS compliant with 2002/95/EC 4.1&4.2 2005/747/EC

Certificate with ISO9001, UL, FCC, CE, RoHs, CB, FDA

Picture	Part No. / Descriptions	Best Seller
	BC-APCA01-SSC050-24 10G SFP+, DAC Active Copper Cable, 5 Meters Conductor 24 AWG	Order 1 week
	BC-APCA01-SSC070-24 10G SFP+, DAC Active Copper Cable, 7 Meters Conductor 24 AWG	Order 1 week
	BC-APCA01-SSC100-24 10G SFP+, DAC Active Copper Cable, 10 Meters Conductor 24 AWG	Order 1 week
	BC-APCA01-SSC010-24 10G SFP+, DAC Active Copper Cable, 1 Meters Conductor 24 AWG	Order 1 week
	BC-APCA01-SSC030-24 10G SFP+, DAC Active Copper Cable, 3 Meters Conductor 24 AWG	Order 1 week

** 24 AWG for Standard Passive, 26/28/30AWG for Other Passive

** Length of Cable depend on customer requested

10G SFP+ DAC Passive Copper Cable

PRODUCT FEATURES

- Truly broadband - operates from 1 to 10.5 Gb/s
- Support hot-pluggable
- Available in lengths from 1m to 7m
- 360 degree cable braid crimp and enhanced EMI skirt
- Low insertion loss and low crosstalk
- Single 3.3V power supply
- RoHS Compliant and Lead-Free
- Compliant with SFF-8472 Rev 11.1
- Compliant with SFP+ MSA: SFF-8431 Rev4.1
- Wire/Cable Type Twinax

APPLICATIONS

- 1/10GbE
- 1/2/4/8x FC
- Infiniband 1X SDR DDR QDR
- Proprietary Interconnects

REGULATORY COMPLIANCE

- ESD to the Electrical PINs: compatible with MIL-STD-883E Method 3015.7
- Immunity compatible with IEC 61000-4-3
- EMI compatible with FCC Part 15 Class B EN55022 Class B
- RoHS compliant with 2002/95/EC 4.1&4.2 2005/747/EC

Certificate with ISO9001, UL, FCC, CE, RoHs, CB, FDA

Picture	Part No. / Descriptions	Best Seller
	BC-APCP01-SSC050-24 10G SFP+, DAC Active Copper Cable, 5 Meters Conductor 24 AWG	Order 1 week
	BC-APCP01-SSC070-24 10G SFP+, DAC Active Copper Cable, 7 Meters Conductor 24 AWG	Order 1 week
	BC-APCP01-SSC100-24 10G SFP+, DAC Active Copper Cable, 10 Meters Conductor 24 AWG	Order 1 week
	BC-APCP01-SSC010-24 10G SFP+, DAC Active Copper Cable, 1 Meters Conductor 24 AWG	Order 1 week
	BC-APCP01-SSC030-24 10G SFP+, DAC Active Copper Cable, 3 Meters Conductor 24 AWG	Order 1 week

** 24 AWG for Standard Passive, 26/28/30AWG for Other Passive

** Length of Cable depend on customer requested

10G SFP+ AOC Active Optical Cable

PRODUCT FEATURES

- Truly broadband - operates from 1 to 10.5 Gb/s
- Support hot-pluggable
- Available in lengths from 1m to 50m
- 360 degree cable braid crimp and enhanced EMI skirt
- Excellent ESD protection
- Single 3.3V power supply
- RoHS Compliant and Lead-Free
- Compliant with SFF-8472 Rev 11.1
- Compliant with SFP+ MSA: SFF-8431 Rev4.1

APPLICATIONS

- 1/10GbE
- 1/2/4/8x FC
- Infiniband 1X SDR DDR QDR
- Proprietary Interconnects

REGULATORY COMPLIANCE

- ESD to the Electrical PINs: compatible with MIL-STD-883E Method 3015.7
- Immunity compatible with IEC 61000-4-3
- EMI compatible with FCC Part 15 Class B EN55022 Class B
- RoHS compliant with 2002/95/EC 4.1&4.2 2005/747/EC

Certificate with ISO9001, UL, FCC, CE, RoHs, CB, FDA

Picture	Part No. / Descriptions	Best Seller
	BC-APCO01-SSC010 10G SFP+, AOC Active Optical Cable 1 Meters	Order 1 week
	BC-APCO01-SSC030 10G SFP+, AOC Active Optical Cable 3 Meters	Order 1 week
	BC-APCO01-SSC050 10G SFP+, AOC Active Optical Cable 5 Meters	Order 1 week
	BC-APCO01-SSC070 10G SFP+, AOC Active Optical Cable 7 Meters	Order 1 week
	BC-APCO01-SSC100 10G SFP+, AOC Active Optical Cable 10 Meters	Order 1 week
	BC-APCO01-SSC150 10G SFP+, AOC Active Optical Cable 15 Meters	Order 1 week

** Lengths of Cable with depend on customer requested.

40G QSFP AOC Active Optical Cable

PRODUCT FEATURES

- 4 independent full-duplex channels
- 1G to 10.3 Gbps data rate per channel
- Support hot-pluggable
- Available in lengths of 1 to 50m
- 360 degree active optical cable braid crimp and enhanced EMI skirt Excellent ESD protection
- Single 3.3V power supply
- RoHS Compliant and Lead-Free
- Compliant with IEEE802.3ba
- Compliant with QSFP+ MSA: SFF-8436

APPLICATIONS

- 40G Ethernet
- Infiniband 4X SDR DDR QDR
- 40G Telecom connections
- Proprietary Interconnects

REGULATORY COMPLIANCE

- ESD to the Electrical PINs: compatible with MIL-STD-883E Method 3015.7
- Immunity compatible with IEC 61000-4-3
- EMI compatible with FCC Part 15 Class B EN55022 Class B (CISPR 22B) VCCI Class B
- RoHS compliant with 2002/95/EC 4.1&4.2 2005/747/EC

Certificate with ISO9001, UL, FCC, CE, RoHs, CB, FDA

Picture	Part No. / Descriptions	Best Seller
	BC-APCO04-QQC010 40G QSFP, AOC Active Optical Cable 1 Meters	Order 1 week
	BC-APCO04-QQC030 40G QSFP, AOC Active Optical Cable 3 Meters	Order 1 week
	APCO04-QQC050 40G QSFP, AOC Active Cable 5 Meters	Order 1 week
	BC-APCO04-QQC070 40G QSFP, AOC Active Cable 7 Meters	Order 1 week
	BC-APCO04-QQC100 40G QSFP, AOC Active Optical Cable 10 Meters	Order 1 week
	BC-APCO04-QQC150 40G QSFP, AOC Active Optical Cable 15 Meters	Order 1 week

** Lengths of Cable with depend on customer requested.

40G-10G QSFP+ AOC Active Optic Cable

PRODUCT FEATURES

- Four-channel full-duplex active optical cable with breakout from QSFP+ to four SFP+
- 1G to 10.5 Gbps data rate per channel
- Support hot-pluggable
- Available in lengths of 1 to 50m
- 360 degree active optical cable braid crimp and enhanced EMI skirt Excellent ESD protection
- Single 3.3V power supply
- RoHS Compliant and Lead-Free
- Complies with QSFP+ and SFP+ MSA form factors
- Commercial operating case temperature range: 0°C to 70°C

APPLICATIONS

- 40G Ethernet
- Infiniband 4X SDR DDR QDR
- Other 40G connection

REGULATORY COMPLIANCE

- ESD to the Electrical PINs: compatible with MIL-STD-883E Method 3015.7
- Immunity compatible with IEC 61000-4-3
- EMI compatible with FCC Part 15 Class B EN55022 Class B (CISPR 22B) VCCI Class B
- RoHS compliant with 2002/95/EC 4.1&4.2 2005/747/EC

Certificate with ISO9001, UL, FCC, CE, RoHs, CB, FDA

Picture	Part No. / Descriptions	Best Seller
	BC-APC004-QSC010 40 Gb/s Active optical cable with breakout from QSFP+ to four SFP+, 1 Meters	Order 1 week
	BC-APC004-QSC020 40 Gb/s Active optical cable with breakout from QSFP+ to four SFP+, 2 Meters	Order 1 week
	BC-APC004-QSC030 40 Gb/s Active optical cable with breakout from QSFP+ to four SFP+, 3 Meters	Order 1 week
	BC-APC004-QSC050 40 Gb/s Active optical cable with breakout from QSFP+ to four SFP+, 5 Meters	Order 1 week
	BC-APC004-QSC070 40 Gb/s Active optical cable with breakout from QSFP+ to four SFP+ 7 Meters	Order 1 week
	BC-APC004-QSC100 40 Gb/s Active optical cable with breakout from QSFP+ to four SFP+, 10 Meters	Order 1 week

** Lengths of Cable with depend on customer requested.

40G-10G QSFP+ DAC Active Optic Cable

PRODUCT FEATURES

- Four-channel full-duplex active copper cable with breakout from QSFP+ to four SFP+
- 1G to 10.5 Gbps data rate per channel
- Support hot-pluggable
- Available in lengths of 1 to 5m
- 360 degree active copper cable braid crimp and enhanced EMI skirt Excellent ESD protection
- Single 3.3V power supply
- RoHS Compliant and Lead-Free
- Complies with QSFP+ and SFP+ MSA form factors
- Commercial operating case temperature range: 0°C to 70°C

APPLICATIONS

- 40G Ethernet
- Fiber Channel
- Infiniband 4X SDR DDR QDR
- SAS (serially connected SCSI)
- Proprietary Interconnects

REGULATORY COMPLIANCE

- ESD to the Electrical PINs: compatible with MIL-STD-883E Method 3015.7
- Immunity compatible with IEC 61000-4-3
- EMI compatible with FCC Part 15 Class B EN55022 Class B
- RoHS compliant with 2002/95/EC 4.1&4.2 2005/747/EC

Certificate with ISO9001, UL, FCC, CE, RoHs, CB, FDA

Picture	Part No. / Descriptions	Best Seller
	BC-APCA04-QSC010-28 40 Gb/s Active copper cable with breakout from QSFP+ to four SFP+, 28AWG, 1 Meters	Order 1 week
	BC-APCA04-QSC020-28 40 Gb/s Active copper cable with breakout from QSFP+ to four SFP+, 28AWG, 2 Meters	Order 1 week
	BC-APCA04-QSC030-28 40 Gb/s Active copper cable with breakout from QSFP+ to four SFP+, 28AWG, 3 Meters	Order 1 week
	BC-APCA04-QSC040-28 40 Gb/s Active copper cable with breakout from QSFP+ to four SFP+, 28AWG, 4 Meters	Order 1 week
	BC-APCA04-QSC050-28 40 Gb/s Active copper cable with breakout from QSFP+ to four SFP+, 28AWG, 5 Meters	Order 1 week
	BC-APCA04-QSC100-28 40 Gb/s Active copper cable with breakout from QSFP+ to four SFP+, 28AWG, 10 Meters	Order 1 week

** Lengths of Cable with depend on customer requested.

40G-10G QSFP+ DAC Passive Optic Cable

PRODUCT FEATURES

- Four-channel full-duplex active copper cable with breakout from QSFP+ to four SFP+
- 1G to 10.5 Gbps data rate per channel
- Support hot-pluggable
- Available in lengths of 1 to 5m
- 360 degree active copper cable braid crimp and enhanced EMI skirt Excellent ESD protection
- Single 3.3V power supply
- RoHS Compliant and Lead-Free
- Complies with QSFP+ and SFP+ MSA form factors
- Commercial operating case temperature range: 0°C to 70°C

APPLICATIONS

- 40G Ethernet
- Fiber Channel
- Infiniband 4X SDR DDR QDR
- SAS (serially connected SCSI)
- Proprietary Interconnects

REGULATORY COMPLIANCE

- ESD to the Electrical PINs: compatible with MIL-STD-883E Method 3015.7
- Immunity compatible with IEC 61000-4-3
- EMI compatible with FCC Part 15 Class B EN55022 Class B
- RoHS compliant with 2002/95/EC 4.1&4.2 2005/747/EC

Certificate with ISO9001, UL, FCC, CE, RoHs, CB, FDA

Picture	Part No. / Descriptions	Best Seller
	BC-APCA04-QSC010-28 40 Gb/s Passive copper cable with breakout from QSFP+ to four SFP+, 28AWG, 1 Meters	Order 1 week
	BC-APCA04-QSC020-28 40 Gb/s Passive copper cable with breakout from QSFP+ to four SFP+, 28AWG, 2 Meters	Order 1 week
	BC-APCA04-QSC030-28 40 Gb/s Passive copper cable with breakout from QSFP+ to four SFP+, 28AWG, 3 Meters	Order 1 week
	BC-APCA04-QSC040-28 40 Gb/s Passive copper cable with breakout from QSFP+ to four SFP+, 28AWG, 4 Meters	Order 1 week
	BC-APCA04-QSC050-28 40 Gb/s Passive copper cable with breakout from QSFP+ to four SFP+, 28AWG, 5 Meters	Order 1 week
	BC-APCA04-QSC100-28 40 Gb/s Passive copper cable with breakout from QSFP+ to four SFP+, 28AWG, 10 Meters	Order 1 week

** Lengths of Cable with depend on customer requested.



BELLCOMMS

FCS

AMP

BTCL

THAI TELECOM

Arrowpipe

Arrowtite

U FLEX

UNION FLEX

UNION

BRADY



NCS NETWORKS COMMUNICATION SOLUTION CO.,LTD.

บริษัท เอ็น ซี เอส เน็ตเวิร์ค คอมมูนิเคชั่น โซลูชั่น จำกัด

39/4-7 Khlong Lamchiak Rd., Nawamin Buengkuam Bangkok Thailand. 10230

39/4-7 ถนนคลองลำเจียก แขวงนาวมินทร์ เขตบึงกุ่ม กรุงเทพมหานคร 10230

Tel : 0-2508-0977 (20 Lines) Fax : 0-2508-0981

www.ncsnetwork.com E-mail: ncs@ncsnetwork.com