

**CCTV accessories**



**BC-102CHD**

CCTV Balan Video

Support HD-CVI, HD-TVI, HD-AHD 720p/1080p and Analog CCTV

**Features**

- Video-Data signals are routed via Twisted Pairs, The unit is a passive (non-amplified) device that allows the transmission of real-time monochrome or color video over Unshielded Twisted-Pair (UTP) and telephone wire.
- Compatible with all HD-CVI, HD-TVI, HD-AHD and analog CCTV
- Up to 450m for 720P CVI Cameras
- Up to 250m for 1080P CVI Cameras
- Up to 250m for 720P/1080P TVI Cameras
- Up to 320m for 720P AHD camera
- Up to 220m for 1080P AHD camera
- Up to 300m for CVBS
- NTSC, PAL, and SECAM video formats
- No power required
- 60dB cross talk and noise immunity
- Compact size and easy installation
- Built-in transient suppression protection

**Technical Specifications**

• Frequency response	DC to 60Mhz
• Attenuation	0.5dB type
• CMMR(Common Mode Rejection Ratio)	60dB,(20K-60M) Hz
• Surge protection	4KV, ESD: 8KV
• Connectors	Male BNC and "Press-Fit" terminal blocks
• Impedance BNC	75 Ohms
• Impedance Terminal	100 Ohms
• Wire type	UTP(22-24AWG) or CAT5E/CAT6
• Working Temperature	-10 C to +70C
• Storage Temperature	-30 to +70 C
• DC loop resistance	29 Ohm/1000ft(9.5Ohm/100m)
• Differential capacitance	19pF/ft max(9.5Ohm/100m)
• Maximum input	1Vp-p
• Humidity	0 to 95%
• Dimension	39mm x 16 mm x 19mm (excluding connectors)
• Material	ABS Plastic

**Application**

