

## Fiber Distribution Unit(FDU) Enclosure



RMS636  
FRONT



RMS636B  
FRONT



RMS72  
FRONT



RMS72  
INSIDE



Bearing Sliding

### DESCRIPTIONS / APPLICATIONS

FDU Enclosures metal steel are designed to provide optimal protection for your fiber optic applications. The enclosures special desinged for protect animal. Another unique feature is the adjustable fiber routing channels. Each fiber channel can be individually adjected to provide ample fiber storage which helps maintain minimum bend radius equirements. Integrated anchoring points provide an excellent form of cable management and cable routing.

#### Features (RMS636, RMS636B)

- 1-36ports with ST,SC,FC and LC Adaptor Connectors.
- Support 3 Snap-Plate
- Material can available metal or aluminium.
- 4 holes 1"diameter for insert Fiber Optic cable.
- Fiber wire management with inside.
- 19" width (compatible Cabinet Rack).
- Provide 4 Cable Gland for 4pcs Lock cable
- Provide 4 Sets of Screw
- Provide M6 Cage Nut and PVC cup washer
- Rodent for protect animals
- White or Black color body

#### Standard

- International : ISO/IEC 11801:2017
- European EN : 50173
- North American : ANSI/TIA/EIA-568.3-D
- Compliant : RoHS

#### Features (RMS72)

- 1-72ports with ST,SC,FC and LC Adaptor Connectors.
- Support 6 Snap-Plate
- 2 holes with cable gland for insert Fiber Optic cable.
- Material can available metal or aluminium.
- Have the window close for keep protected with Patch cable
- Have the hole for put Fiber wire management with inside.
- 19" width (compatible Cabinet Rack).
- Easy to sliding with Bearing
- Provide 4 Sets of Screw
- Provide M6 Cage Nut and PVC cup washer
- Rodent for protect animals.
- White or Black color body.



RMS48  
FRONT



RMS48  
INSIDE



Bearing Sliding

#### Features (RMS48)

- 1-48 ports with ST,SC,FC and LC Adaptor Connectors.
- Support 4 Snap-Plate
- 2 holes with cable gland for insert Fiber Optic cable.
- Material can available metal or aluminium.
- Have the window close for keep protected with Patch cable
- Have the hole for put Fiber wire management with inside.
- 19" width (compatible Cabinet Rack).
- Easy to sliding with Bearing
- Provide 4 Sets of Screw
- Provide M6 Cage Nut and PVC cup washer
- Rodent for protect animals.
- White or Black color body.



RMS636CF  
FRONT

#### Features (RMS636CF)

- 1-36ports with ST,SC,FC and LC Adaptor Connectors.
- Support 3 Snap-Plate
- Support 2 Pieces of Splice Tray
- 4 holes 1"diameter for insert Fiber Optic cable.
- Have the hole for Fiber wire management with inside.
- 19" width (compatible Cabinet Rack).
- Rodent for protect animals
- Provide 4 Cable Gland for 4pcs Lock cable
- Provide 4 Sets of Screw
- Provide M6 Cage Nut and PVC cup washer
- Have the window close for keep protected with Patch cable
- White color body

Part Number.	Descriptions
RMS636	1U FDU Enclosure 36 port, Siliding,(43 x 26 x 4.5 cm) White color
RMS636B	1U FDU Enclosure 36 port, Siliding,(43 x 26 x 4.5 cm) Black color
RMS636CF	1U FDU Enclosure 36 port, Siliding,(43 x 26 x 4.5 cm) White color
RMS48	2U FDU Enclosure 48 port, Siliding,(43 x 32 x 9.0 cm) White color
RMS72	3U FDU Enclosure 72 port, Siliding,(43 x 32 x 13.5 cm) White color