

Fiber Distribution Unit(FDU) Enclosure, Wall type



WM624
FRONT



WM648
FRONT



WM624
INSIDE



WM648
INSIDE

DESCRIPTIONS / APPLICATIONS

FDU Enclosures metal steel are designed to provide optimal protection for your fiber optic applications. The enclosures special desinged for protect animal. Another unique feature is the adjustable fiber routing channels. Each fiber channel can be individually adjected to provide ample fiber storage which helps maintain minimum bend radius equirements. Integrated anchoring points provide an excellent form of cable management and cable routing.

Features (WM624)

- 1-24 ports with ST,SC,FC and LC Adaptor Connectors
- Support 2 Snap-Plate
- 4 holes with 2 cable gland for insert Fiber Optic Cable
- 2 holes 1" diameter for insert Fiber Optic Patch cable.
- Material can available metal or aluminium.
- Fiber wire management with inside.
- Front has pop-up Key locked
- Two doors can open
- Rodent steel for protect animals
- Dimension 30 x 30 x 5.0 cm.
- White or Black color body

Standard

- International : ISO/IEC 11801 : 2017
- European EN : 50173
- North American : ANSI/TIA/EIA-568.3-D

Features (WM648)

- 1-48ports with ST,SC,FC and LC Adaptor Connectors.
- Support 4 Snap-Plate
- 4 holes with 2 cable gland for insert Fiber Optic Cable.
- 2 holes 1" diameter for insert Fiber Optic Patch cable.
- Material can available metal or aluminium.
- Fiber wire management with inside.
- Front has Key locked
- Two doors can open.
- Rodent for protect animals.
- Dimension 30 x 30 x 8.5 cm.
- White or Black color body.

Part Number.	Descriptions
WM624	24 ports FDU Enclosure, Wallmount Type,Support 2 Snap-Plate, Dimension with 30 x 30 x 5.0cm., White color
WM648	48 ports FDU Enclosure, Wallmount Type,Support 4 Snap-Plate, Dimension with 30 x 30 x 8.5cm., White color