

24 10/100Base-TX ports and 2 Gigabit Combo Ports (SFP+RJ45)

Product Description:

The SMD-2402 is a 24+2G network Switch which is designed by Shenzhen Hi-Net Technology Company. It is designed for residential building in the corridor-level broadband switching equipment, for the edge of the access and LAN to provide high-quality network connections.

The S2026 is 19" case-shaped device with 1U high. It provides 24 10/100 Base-TX ports and 2 Gigabit Combo Ports (SFP+RJ45). The S2026 can provide you an easy, economic, high-performance solution for networking, which is your ideal choice for high-speed networking.

Product Features:

- IEEE802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z
- Provides 24 10/100Base-TX ports and 2 Gigabit Combo Ports (SFP+RJ45)
- 8K MAC address table
- High back-plane bandwidth 8.8Gbps
- 19" rack-mounted metal case
- Build-in industrial power supplies
- IEEE802.3x Flow control
- Surge protection for power port and data ports
- Plug and play, no configuration required
- EMI standards complies with FCC, CE class B



Products Specifications:

Item	Description
Summarize	
Fixed port	24 10/100Base-TX ports and 2 Gigabit Combo Ports (SFP+RJ45)
LED Indicators	PWR, Speed, Link/Act VLAN LED.
Input voltage	100V~240V AC, 50/60Hz
Transmission Method	Store and Forward
Forwarding Speed	10Mbps : 14880pps 100Mbps : 148800pps 1000Mbps : 1488000pps
Power consumption	5W
Operating temperature	0°C~40°C.
Storage temperature	-10°C~70°C.
Relative humidity	20%~85% (non-condensing).
Thermal methods	Fanless.
Switching capacity	8.8G.
MAC address table	8K.
Traffic control	IEEE 802.3x full-duplex flow control.
Package	
Unit Size	44*20*4.4cm
Weight	<3KG
package	Carton Box S2026 Network Switch User Manual Warranty Card Power Cord*1 Rack Mount Kit*2 Rubber Feet*4
Package	